



# TANDBERG 8000 MXP

For the boardroom. Sleek, elegant design combined with state-of-the-art engineering. The most advanced features and functions for mission critical communication. 50" plasma screens and a best-in-class, CD quality, stereo audio system provide the ultimate video experience.



Digital NAM adds performance and clarity with true CD-quality audio.

**PROTECT YOUR TECHNOLOGY INVESTMENT. EXTEND THE LIFETIME OF YOUR PRODUCTS.** TANDBERG's Constant Care Services fulfill customers' support needs from decision through deployment and beyond.

#### DESIGN FEATURES

- Designed for boardroom applications
- Dual 50" plasma monitors with 16:9 widescreen format
- Sleek slim-line stand with monitors, camera, remote control, microphones and cabling
- Wide angle view camera with extensive zoom, pan and tilt
- CD quality, stereo audio and the Digital NAM are enhanced by an optional satellite speaker system ensure a superior audio experience

#### APPLICATION FEATURES

- Join up to 6 video and 5 audio sites with optional embedded MultiSite functionality
- Best possible call for each MultiSite participant with rate matching and transcoding
- Powerful live presentations through one-step PC plug-in or LAN connection
- View presentations and presenter simultaneously with either DuoVideo or H.239
- TANDBERG Expressway™ Technology
- URI Dialing
- H.323, H.320 & SIP support

#### PERFORMANCE FEATURES

- Choice of network: IP, ISDN and other external network
- Bandwidth: up to 2 Mbps ISDN/ 4 Mbps IP (6 Mbps in MultiSite)
- Superior video quality incorporating the H.264 standard
- True CD-quality, stereo audio
- Standards-based embedded encryption (AES & DES)
- Protection against network interruptions in point-to-point and multipoint calls with automatic Downspeeding and IPLR

#### UNIT DELIVERED COMPLETE WITH:

2 x 50" wide-screen plasma monitors, wireless remote control, Tracker, W.A.V.E. II camera, microphone, Digital Audio Module™, integrated cabling and stand and Optional Satellite Stereo Speakers

#### MONITORS

Dual 50" plasma screens  
16:9 high resolution widescreen format

#### BANDWIDTH

H.320 up to 2 Mbps  
H.323 up to 4 Mbps point-to-point  
SIP up to 4 Mbps  
Up to 6 Mbps total MultiSite bandwidth

#### FIREWALL TRAVERSAL

TANDBERG Expressway Technology™  
Auto NAT

#### VIDEO STANDARDS

H.261, H.263, H.263+, H.263++ (Natural Video), H.264

#### VIDEO FEATURES

Native 16:9 Widescreen  
Advanced Screen Layouts  
Picture in Picture (PIP)  
Picture outside Picture (POP)  
Side by Side  
PC Zoom  
Intelligent Video Management  
Simultaneous videoconference & local PC mode

#### VIDEO INPUTS (5 INPUTS)

1 x MiniDin, S-video: main camera  
1 x MiniDin, S-video: auxiliary / document camera  
1 x RCA / Phono, composite: document camera / aux  
1 x RCA / Phono, composite: VCR  
1 x DVI/SXGA: PC  
Input: 800 x 600 @ 60, 72, 75, 85 Hz, 1024 x 768 @ 60, 70, 75 Hz, 1280 x 720 @ 60Hz  
Extended Display Identification Data (EDID)

#### VIDEO OUTPUTS (6 OUTPUTS)

1 x MiniDin, S-video: main monitor  
1 x MiniDin, S-video: dual monitor  
1 x RCA / Phono, composite: main monitor or VCR  
1 x RCA / Phono, composite: dual monitor or VCR  
2 x DVI/XGA: main and dual monitor  
XGA Output  
800 x 600 @ 75 Hz, 1024 x 768 @ 60 Hz,  
1280 x 768 (WXGA) @ 60 Hz  
VESA Monitor Power Management

#### VIDEO FORMAT

NTSC, PAL, VGA, SVGA, XGA, W-XGA, or SXGA

#### LIVE VIDEO RESOLUTIONS

##### NATIVE NTSC:

4SIF (704 x 480 pixels), Digital Clarity  
Interlaced SIF (352 x 480 pixels), Natural Video  
SIF (352 x 240 pixels)

##### NATIVE PAL:

4CIF (704 x 576 pixels), Digital Clarity  
Interlaced CIF (352 x 576 pixels), Natural Video  
CIF (352 x 288 pixels)  
QCIF (176 x 144 pixels)  
SQCIF (128 x 96 pixels) decode only

##### NATIVE PC RESOLUTIONS:

XGA (1024 x 768)  
SVGA (800 x 600 pixels)  
VGA (640 x 480 pixels)

#### STILL IMAGE TRANSFER

CIF, SIF, 4CIF (H.261 Annex D), 4SIF, VGA, SVGA, XGA

#### AUDIO STANDARDS

G.711, G.722, G.722.1, G.728, 64 bit & 128 bit MPEG4 AAC-LD

#### AUDIO FEATURES

CD-Quality 20 KHz Mono and Stereo  
Telephone add-on via MultiSite  
Four separate acoustic echo cancellers  
Audio mixer  
Automatic Gain Control (AGC)  
Automatic Noise Reduction  
Audio level meters  
VCR ducking  
Stereo Speakers  
Packet loss management  
Active lip synchronization

#### AUDIO INPUTS (4 INPUTS)

3 x microphone, 24V phantom powered, XLR connector, each with separate echo cancellers  
1 x RCA / Phono, Line Level: separate echo canceller  
1 x RCA / Phono, Line Level: auxiliary (or VCR/DVD Stereo L)  
1 x RCA / Phono, Line Level: VCR/DVD (Stereo R)

#### AUDIO OUTPUTS (3 OUTPUTS)

1 x RCA / Phono, S/PDIF (mono/stereo) or Analogue Line Level: main audio or Analogue Stereo L  
1 x RCA / Phono, Line Level: auxiliary (or Analogue Stereo R or VCR Stereo L)  
1 x RCA / Phono, Line Level: VCR (mono or Stereo R)

#### FRAME RATES

30 frames per second @ 168 kbps and above  
60 fields per second @ 336 kbps and above (Point-to-point)

#### DUAL STREAM

Duo Video & H.239  
Available on H.323 & H.320  
Available in Multisite from any site

#### NETWORK FEATURES

Auto H.320 / H.323 dialing  
SIP  
Downspeeding  
Programmable network profiles

#### Intelligent Call Management

HO on ISDN-PRI Facility  
Maximum call length timer  
Automatic SPID and line number configuration (National ISDN, GR-2941-CORE)  
SoftMux  
NATO standard KG194 / KIV-7 encryptor support  
H.331 Broadcast Mode  
URI Dialing

#### MULTISITE FEATURES

H.323/H.320/SIP/Telephony/VoIP in the same conference  
Audio and Video Transcoding  
Video rate matching from 56 kbps - maximum conference rate  
CP4, CP 5 + 1 and Voice Switched  
Best Impression (Automatic CP Layouts)  
H.264, Encryption, Digital Clarity  
Dual Stream from any site  
ISDN & IP Downspeeding and IPLR  
MultiSite (H.243) Cascading on H.320 & H.323  
Dial in / Dial out  
Chair control for host system  
Snapshot of ongoing conference (JPEG)  
Snapshot of ongoing DuoVideo/H.239 presentation (JPEG)  
Separate welcome page for encrypted conferences  
Conference rates up to 6 Mbps  
Up to 6 video and 5 audio sites  
4 sites @ 2 Mbps, 6 sites @ 768 (+telephone calls)  
Mix ISDN (BRI or PRI), or Serial Interface (V.35) with IP up to maximum conference rate

#### EMBEDDED ENCRYPTION

H.320 and H.323 point-to-point and multipoint calls  
Standards-based: H.233, H.234, H.235 v2&v3, DES and AES  
NIST-validated AES  
NIST-validated DES  
Automatic key generation and exchange  
Supported in Dual Stream & MultiSite

#### IP NETWORK FEATURES

H.235 Authentication  
Differentiated Services (DiffServ)  
Resource Reservation Protocol (RSVP)  
IP precedence  
IP type of service (ToS)  
IP adaptive bandwidth management (including flow control)  
Auto gatekeeper discovery  
Dynamic playout and lip-sync buffering  
Intelligent Packet Loss Recovery (IPLR)  
H.245 DTMF tones in H.323  
Cisco Call Manager integration using ECS  
IP Address Conflict Warning

#### SECURITY FEATURES

Management via HTTPS  
IP Administration Password  
Menu Administration Password  
Dialing Access code  
Streaming password  
H.243 MCU Password  
VNC password  
SNMP security alerts  
Disable IP services  
MD-5 Challenge  
Network Settings protection  
SIP Authentication via NTLM

#### NETWORK INTERFACES

6 x ISDN BRI (RJ-45), S-interface  
1 x E1 / T1 G.703 (RJ-45) for ISDN PRI or Leased E1 / T1  
1 x E1 / T1 G.703 (RJ-45) for future usage  
1 x LAN / Ethernet (RJ-45) 10/100 Mbit (LAN / DSL /cable modem)  
1 x X.21 / V.35 / RS-449 with RS-366 dialing, Leased Line or data triggered mode  
1 x USB

#### ETHERNET / INTERNET / INTRANET CONNECTIVITY

TCP / IP, DHCP, ARP, FTP, Telnet, HTTP, HTTPS, SOAP and XML, MD-5 Challenge  
SNMP Enterprise Management  
Internal web server  
Internal streaming server

#### OTHER MAJOR STANDARDS SUPPORTED

H.231, H.233, H.234, H.235 v2&v3, H.239, H.241, H.243, H.281, BONDING (ISO 13871), H.320, H.323, H.331  
RFC 3261, RFC 2237, RFC 3264, RC 3311, RFC 3550, RFC 2032, RFC 2190, RFC 2429, RFC 3407

#### W.A.V.E. (WIDE ANGLE VIEW) II CAMERA

10 x zoom 1/4" CCD +15° / -20° tilt  
+ / -95° pan  
61° vertical field of view  
96° total vertical field of view  
77° horizontal field of view  
267° total horizontal field of view  
460 (PAL) / 470 (NTSC) TV lines  
Min. illumination 2 Lux (F1.8)  
Auto or manual focus / brightness / white balance  
Far-end camera control  
15 near and far-end camera pre-sets  
Voice-activated camera positioning  
Daisy chain support for up to 4 cameras

#### CLOSED CAPTIONING/TEXT CHAT

T.140 text chat available from RS-232, Telnet, Web and User Interface

#### PRESENTATIONS AND COLLABORATION

Natural Presenter Package including:  
PC Presenter (DVI-I, SXGA In)  
PC SoftPresenter  
Digital Clarity & Native Formats  
Advanced Video Layouts

Streaming compatible with Cisco IP/TV,  
Apple QuickTime®, RealPlayer® v8 etc.

#### SYSTEM MANAGEMENT

Support for the TANDBERG Management Suite  
Total management via embedded web server, SNMP, Telnet, XML, SOAP and FTP  
Remote software upload: via web server or FTP server  
1 x RS-232 local control and diagnostics  
Remote control and on-screen menu system

#### DIRECTORY SERVICES

Support for Local, Global and Dynamic Server Directories  
Unlimited entries using Server directory supporting LDAP and H.350\*  
400 number global directory  
200 number local directory  
16 dedicated MultiSite entries  
Call History  
Directories in Local Languages

#### 19 SELECTABLE MENU LANGUAGES

Simplified Chinese, Traditional Chinese, English, French, German, Italian, Japanese, Korean, Norwegian, Portuguese, Russian, Spanish and Swedish

#### CUSTOMIZED WELCOME SCREEN AND COMPANY LOGO

#### POWER

100 - 250 VAC, 50 - 60 Hz 65 watts max. for codec and main camera  
500 watts max. per monitor  
250 watts for DNAM

#### OPERATING TEMPERATURE AND HUMIDITY

0° C to 35° C (32° F to 95° F) ambient temperature  
10% to 90% Relative Humidity (RH)

#### STORAGE AND TRANSPORT TEMPERATURE

-20° C to 60° C (-4° F to 140° F) at RH 10-90% (non-condensing)

#### APPROVALS

Directive 73/23/EEC (Low Voltage Directive)  
-Standard EN 60950

Directive 89/336/EEC (EMC Directive)

-Standard EN 55022, Class B

-Standard EN 55024

-Standard EN 61000-3-2/-3-3

Directive 1999/5/EEC (R&TTE Directive)

-Standard TBR3

-Standard TBR4

Approved according to UL 60950

and CAN/CSA C22.2 No. 60950

Complies with FCC15B Class B

#### FOOTPRINT

Width: 33.9" / 86 cm Depth: 29.1" / 74 cm

\* Requires TANDBERG Management Suite version 9.0 or newer

System features vary depending on network selection and software package. All specifications subject to change without notice.

TANDBERG is a registered trademark or trademark of TANDBERG in the U.S. and other countries.

Cisco, Cisco Systems, the Cisco Systems logo, and the Cisco Arrow logo are registered trademarks or trademarks of Cisco Systems, Inc. and/or its affiliates in the U.S. and certain other countries.

RealPlayer is a trademark or a registered trademark of RealNetworks, Inc.

QuickTime is a registered trademark of Apple Computer, Inc., registered in the U.S. and other countries.

Microsoft and NetMeeting are either registered trademarks or trademarks of Microsoft Corporation in the United States and/or other countries.

All other trademarks are property of their respective owners.

Contains iType™ from Agfa Monotype Corporation.

All photographs and images contained in these materials are for general, representational purposes only. Actual products may differ based upon component availability.

Service availability may vary from region to region. Please contact your TANDBERG reseller for more information.

## TANDBERG

# 8000

## MPX

#### TANDBERG WORLD HEADQUARTERS

Philip Pedersens vei 22  
1366 Lysaker, Norway  
Tel: +47 67 125 125  
Fax: +47 67 125 234  
Video: +47 67 117 777  
E-mail: tandberg@tandberg.net

200 Park Avenue, Suite 2005  
New York, NY U.S.A. 10166  
Tel: +1 212 692 6500  
Tel: +1 800 538 2884 (toll free in the U.S.)  
Fax: +1 212 692 6501  
Video: +1 212 692 6535  
E-mail: tandberg@tandbergusa.com

July 2005